







küschall® Champion



Live without boundaries...

küschall Champion Aluminium

The küschall Champion Aluminium provides you with all possibilities: colours, configurations, options. There are almost unlimited ways to personalize your wheelchair. Now available with adduction frame, the wheelchair offers better leg support and increased maneuverability. Express yourself!



Technical Data



Seat width:
340 – 460 mm
in increments
of 20 mm



Seat depth:
340 – 460 mm
in increments
of 20 mm



Seat height:
front: 450 – 540 mm
rear: 390 – 490 mm
in increments of 10 mm



Backrest height:
300 – 465 mm
in increments of 15 mm



Knee-to-heel length:
220 – 500 mm
in increments
of 10 mm



Backrest angle:
79°/83.5°/88°/
92.5°/97°



Total width:
SW + 170 mm



Total width folded:
approx. 300 mm



Total length:
75°: approx. 860 mm
90°: approx. 810 mm



Total weight
unloaded:
approx. 10.7 kg





Max. user weight:
120 kg



Transport weight
w/out rear wheels:
approx. 7.7 kg

Küschall Champion Titanium

What could better represent the longevity than Titanium? For the first time in its 25 years of success, the küschall Champion comes with a new titanium frame. If you are looking for a strong, scratch-resistant and stylish material, then the küschall Champion Titanium is exactly what you need! On top of this, the küschall Champion Titanium has carbon front wheel supporters – a real eye catcher!



Technical Data



Seat width:
340 – 460 mm
in increments
of 20 mm



Seat depth:
340 – 460 mm
in increments
of 20 mm



Seat height:
front: 450 – 540 mm
rear: 390 – 490 mm
in increments of 10 mm



Backrest height:
300 – 465 mm
in increments of 15 mm



Knee-to-heel length:
220 – 500 mm
in increments
of 10 mm



Backrest angle:
79°/83.5°/88°/
92.5°/97°



Total width:
SW + 170 mm



Total width folded:
approx. 300 mm



Total length:
75°: approx. 860 mm
90°: approx. 810 mm



Total weight
unloaded:
approx. 10.1 kg



Max. user weight:
120 kg



Transport weight
w/out rear wheels:
approx. 7.1 kg



Küschall Champion Carbon

Carbon has always been the symbol of elegance for high level products. Exceptionally strong, reliable and lightweight, the küschall Champion Carbon combines design and performance! Get full attention!



6
C
Carbon

Technical Data



Seat width:
340 – 460 mm
in increments
of 20 mm



Seat depth:
400 – 460 mm
in increments
of 20 mm



Seat height:
front: 450 – 540 mm
rear: 390 – 490 mm
in increments of 10 mm



Backrest height:
300 – 465 mm
in increments of 15 mm



Knee-to-heel length:
300 – 340 mm
and 400 – 500 mm
in increments of 10 mm



Backrest angle:
79°/83.5°/
88°/92.5°/97°



Total width:
SW + 170 mm



Total width folded:
approx. 300 mm



Total length:
85°: approx. 840 mm



Total weight
unloaded:
approx. 10.1 kg



Max. user weight:
120 kg



Transport weight
w/out rear wheels:
approx. 7.1 kg

Küschall Champion: 25 years of success

In 1986 Küschall invented the first foldable wheelchair with the performance & design of a rigid wheelchair. The unique and revolutionary folding mechanism of the küschall Champion changed the life of thousands users. Freedom, mobility – an independent life!


Still as reliable as it was 25 years ago, the küschall Champion is your perfect travel companion!



Küschall AG | Benkenstrasse 260 | CH-4108 Witterswil | Switzerland | Phone +41 (0) 61 487 70 70 | Fax +41 (0) 61 487 70 79 | www.kuschall.com

United Kingdom: Invacare Ltd. | Pencoed Technology Park, Pencoed, Bridgend | CF35 5HZ Phone +44 (0) 1656 776222 | Fax +44 (0) 1656 776220 | www.invacare.co.uk

Ireland: Invacare Ltd. | Unit 5, Seatown Business Campus | Seatown Road | Swords, Co. Dublin | Phone +353 (0)1 810 7084 | Fax +353 (0)1 810 7085 | www.invacare.co.uk

 Join us on facebook and get the very latest news about küschall

küschall® is a registered trademark. Every effort has been made to ensure that the contents of this publication are fully up-to-date at the time of going to print. As part of its ongoing improvement of products, Küschall AG reserves the right to modify existing models at any time. Any use of this publication, or of parts thereof, as well as any reproduction of images, must have the written consent of Küschall AG.